

SUPER BLUE 2 LT™

Featuring STRIPENET® anti-marking, anti-static nets

INSTALLATION

instructions

ANTI-MARKING, ANTI-STATIC SYSTEM FOR KOMORI LITHRONE 20", 26" & 40" TRANSFER CYLINDERS

Read all instructions thoroughly before beginning installation.

1. Remove any existing materials mounted to the transfer cylinders that will be converted to the Super Blue® LT™ anti-marking system.
2. Clean the transfer cylinder surface(s) using a solvent. Remove any grease, dried ink, oil or dust build up on the surface of the transfer cylinders, including the gutter areas.
3. After cleaning the transfer cylinder surface, wipe once again with a clean dry cloth to remove any excess solvent.
4. Once the surfaces are cleaned, rotate the transfer cylinder to access the gripper edge clamping bar. (See Figure 1.)
5. Loosen (but do not completely remove) the spring-loaded flat head screws enough to allow the Super Blue® LT™ system to slide under the clamping bar. As the screws are loosened the springs should raise the clamping bar. (See Figure 1.)




Figure 1

Super Blue and Super Blue 2 and StripeNet are registered trademarks of PRI. Super Blue LT is a trademark of PRI. All other company and product names mentioned in this document are trademarks of their respective companies. Copyright © 2003, Printing Research, Inc. All Rights Reserved. Covered by U.S. and Foreign Patents.



PRI
10954 Shady Trail, Dallas, TX 75220 USA
(800) 627-5537 or (214) 353-9000, Fax: (214) 357-5847
www.superblue.net

6. Insert the Super Blue[®] LT™ system under the gripper clamping bars approximately 1/8" to 3/16". Be sure that the Super Blue[®] LT™ system is centered on the transfer cylinder and tighten the flat head screws. (See Figure 2.)




Figure 2

7. Holding the tail edge of the Super Blue[®] LT™ system, rotate the transfer cylinder until the tail clamping bar is accessible.
8. Loosen (but do not completely remove) the spring-loaded flat head screws enough to allow the Super Blue[®] LT™ system to slide under the tail-edge clamping bar. As the screws are loosened the springs should raise the clamping bar.
9. Insert the Super Blue[®] LT™ base cover under the tail clamp bar. Be sure that the Super Blue[®] LT™ base cover is centered on the transfer cylinder and tighten the flat head screws. The Super Blue[®] LT™ base cover must be installed tightly between gripper and tail clamps to ensure there are no wrinkles or base cover movement. *Please Note: While the base cover is tight the StripeNet[®] anti-marking, anti-static material will remain loose.*
10. Rotate the cylinder and inspect the Super Blue[®] LT™ base cover being sure that it is laying smoothly on the transfer cylinder surface without any wrinkles.
11. Repeat this process for all remaining transfer cylinders.